

ELECTRIC MOTOR DRIVE



- ⚡ Optimization and match of hydraulic system delivers longer lasting performance
- ⚡ Optimized electronic control system for better brake ability on a long downhill
- ⚡ Improved steering mechanism reduces tire wear during turning
- ⚡ Battery powered with zero emission and environmental-friendly

PRODUCT SPECIFICATION

Model	AS0607E	AS0808E	AS0812E	AS1012E	AS1212E
Lift Capacity	230kg	230kg	450kg	320kg	320kg
Lift Capacity Extension	120kg	113kg	113kg	113kg	113kg
Max. Platform Occupants	2	2	2	2	2
Max. Working Height(A+2)	7.8m	10m	10m	12m	14m
Overall Length(B)	1.86m	2.47m	2.47m	2.47m	2.47m
Overall Width(C)	0.76m	0.83m	1.18m	1.18m	1.18m
Overall Height-guardrail unfolded	2.1m	2.27m	2.28m	2.4m	2.56m
Overall Height-guardrail folded	1.73 m	1.96m	1.68m	1.8m	1.96m
Platform Extension Length	0.9m	0.9m	0.9m	0.9m	0.9m
Driving Speed (stowed/raised)	4/0.8km/h	4/0.8km/h	4/0.8km/h	4/0.8km/h	4/0.8km/h
Up/Down Speed-GB	16/34sec	31/40sec	/	58/48sec	58/60sec
Up/Down Speed-CE	16/34sec	30/39sec	35/40sec	58/48sec	58/60sec
Gradeability	25%	25%	25%	25%	25%
Max. Slope	1.5°/3°	1.5°/3°	1.5°/3°	2°/3°	1.5°/3°
Machine Weigh	1560kg	2180kg	2715kg	3000kg	3300kg

